



Un subwoofer fuori dagli schemi. Capace di riprodurre le basse frequenze con profondità, estensione e controllo.

La configurazione con radiatore passivo caricato nella parte inferiore del cabinet costituisce la soluzione ottimale per ogni problema di inserimento in ambiente.

*An extraordinary subwoofer. Capable of reproducing bass frequencies with depth, extension and control.*

*The configuration with a passive radiator loaded in the lower part of the cabinet is the best solution for any problems regarding insertion into the interior.*

### SYSTEM

Active subwoofer with passive radiator.

### CABINET

Construction with de-coupled side panels for resonances control.

### WOOFERS

300 mm hard paper cone, magnetically shielded, 260 mm passive radiator.

### FEATURES

200 watt mosfet amplifier.

Dynamic limiter negative temperature coefficient.

RCA & XLR inputs.

Low-pass filter 24 dB per Octave.

Switchable low-pass filter from 38 Hz to 65 Hz – 6 positions.

High-pass filter 20 Hz. Soft start.

Overcurrent and thermal protection.

Phase reverse switch.

115 V and 230 V.

### FINISH

Combination of black leather and teak or black piano lacquer.

### DIMENSIONS

360 x 370 x 470 mm (WxDxH).

### WEIGHT

25.5 Kg – net weight/28 Kg – shipping weight.